

DN2302S

DN2302S N-Channel MOSFET

General description


N-Channel MOSFET

FEATURES

- $V_{DS}=20V$
- $I_D=3.2A$
- $R_{DS(ON)}$ (at $V_{GS}=4.5V$) $<60\ m\Omega$
- $R_{DS(ON)}$ (at $V_{GS}=2.5V$) $<80\ m\Omega$
- Trench Power MOSFET technology
- High Power and current handing capability
- High density cell design for low $R_{DS(ON)}$

APPLICATIONS

- DC-DC Converters
- LED Driver
- Switching Circuits



Device Marking Code:

Device Type	Device Marking
DN2302S	A2sHB

Absolute Maximum Ratings

Parameters	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	20	V
Gate-Source Voltage	V_{GS}	± 10	V
Continuous Drain Current	I_D	3.2	A
Pulsed Drain Current (note 1)	I_{DM}	12.8	A
Maximum Power Dissipation	P_D	1.0	W
Thermal Resistance from Junction to Ambient (note 2)	$R_{\theta JA}$	125	$^{\circ}C/W$
Junction and Storage Temperature	T_J, T_{STG}	-50~+150	$^{\circ}C$

DN2302S

Electrical Characteristics

Parameters	Symbol	Test Condition	Min	Typ	Max	Unit
Static Characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	20	--	--	V
Zero gate voltage drain current	I_{DSS}	$V_{DS} = 20V, V_{GS} = 0V$	--	--	1	μA
Gate-body leakage current	I_{GSS}	$V_{GS} = \pm 10V, V_{DS} = 0V$	--	--	± 100	nA
Gate threshold voltage (note 3)	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	0.4	0.6	1.0	V
Drain-source on-resistance (note 3)	$R_{DS(on)}$	$V_{GS} = 4.5V, I_D = 3A$	--	48	60	m Ω
		$V_{GS} = 3.3V, I_D = 2A$	--	55	70	m Ω
		$V_{GS} = 2.5V, I_D = 1A$	--	66	80	m Ω
Diode forward voltage (note 3)	V_{SD}	$I_S = 1A, V_{GS} = 0V$	--	0.82	1.2	V

Dynamic Characteristics (note4)						
Input Capacitance	C_{iss}	$V_{DS} = 10V, V_{GS} = 0V, f = 1MHz$	--	160	--	pF
Output Capacitance	C_{oss}		--	30	--	pF
Reverse Transfer Capacitance	C_{rss}		--	25	--	pF
Switching Characteristics (note 4)						
Turn-on delay time	$t_{d(on)}$	$V_{DD} = 10V, I_D = 2A, R_G = 3.3\Omega, V_{GS} = 4.5V$	--	8	--	ns
Turn-on rise time	t_r		--	30	--	ns
Turn-off delay time	$t_{d(off)}$		--	19	--	ns
Turn-off fall time	t_f		--	28	--	ns
Total Gate Charge	Q_g	$V_{DS} = 10V, I_D = 3A, V_{GS} = 5V$	--	4.0	--	nC
Gate-Source Charge	Q_{gs}		--	0.4	--	nC
Gate-Drain Charge	Q_{gd}		--	1.2	--	nC

Note :

- 1) Repetitive rating: Pulse width limited by maximum junction temperature
- 2) Surface Mounted on FR4 board, $t \leq 10$ sec.
- 3) Pulse test : Pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.
- 4) Guaranteed by design, not subject to production.

Typical Characteristics




Fig1. Typical Output Characteristics




Fig2. Normalized Threshold Voltage Vs. Temperature




Fig3. Typical Transfer Characteristics




Fig4. Drain-Source Voltage vs Gate-Source Voltage




Fig5. Typical Source-Drain Diode Forward Voltage
www.doeshare.net




Fig6. Maximum Safe Operating Area



DN2302S




Fig7. Typical Capacitance Vs. Drain-Source Voltage






Fig8. Typical Gate Charge Vs. Gate-Source Voltage

SOT-23 Package information



Symbol	Dimensions in Millimeter		Dimensions in Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950Type		0.037Type	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.220REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

SOT-23 Suggested Pad Layout



Important Notice and Disclaimer

DOESHARE has used reasonable care in preparing the information included in this document, but DOESHARE does not warrant that such information is error free. DOESHARE assumes no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.

DOESHARE no warranty, representation or guarantee regarding the documents, circuits and products specification, DOESHARE reservation rights to make changes for any documents, products, circuits and specifications at any time without notice.

Purchasers are solely responsible for the choice, selection and use of the DOESHARE products and services described herein, and DOESHARE assumes no liability whatsoever relating to the choice, selection or use of the products and services described herein.

No license, express or implied, by implication or otherwise under any intellectual property rights of DOESHARE.

Resale of DOESHARE products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by DOESHARE for the DOESHARE product or service described herein and shall not create or extend in any manner whatsoever, any liability of DOESHARE.