

2N7002KDW

2N7002KDW SOT-363 Plastic-Encapsulate MOSFET


General description

SOT-363 Plastic-Encapsulate MOSFET

FEATURES

- High density cell design for low $R_{DS(ON)}$.
- Voltage controlled small signal switch.
- Rugged and reliable.
- High saturation current capability.
- ESD protected
- Load Switch for Portable Devices.
- DC/DC Converter.
- SOT-363 Small Outline Plastic Package
- Epoxy UL: 94V-0
- Mounting Position: Any

SOT-363



1. Source1
2. Gate1
3. Drain2
4. Source2
5. Gate2
6. Drain1

DEVICE MARKING: 72K

Absolute Maximum Ratings (Ta=25°C unless otherwise specified)

Parameters	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	60	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current	I_D	340	mA
Power Dissipation	P_D	150	mW
Junction Temperature	T_j	150	°C
Storage Temperature	T_{stg}	-55~+150	°C
Thermal Resistance From Junction to Ambient	$R_{\theta JA}$	833	°C/W

Maximum Ratings & Thermal Characteristics (Ratings at 25°C ambient temperature unless otherwise specified.)


Parameter	Symbols	Test Condition	Limits			Unit
			Min	Typ	Max	
Drain-Source Breakdown Voltage	V_{DS}	$V_{GS}=0V, I_D=250\mu A$	60			V
Gate-Threshold voltage*	V_{th(GS)}	$V_{DS}=V_{GS}, I_D=1mA$	1	1.3	2.5	V
Gate-body Leakage	I_{GSS1}	$V_{DS}=0V, V_{GS}=\pm 20V$			± 10	μA
Zero Gate Voltage Drain current	I_{DSS}	$V_{DS}=48V, V_{GS}=0V$			1	μA
Drain-Source On-Resistance*	R_{DS(ON)}	$V_{GS}=10V, I_D=500mA$		0.9	5	Ω
		$V_{GS}=4.5V, I_C=200mA$		1.1	5.3	
Diode Forward voltage	V_{SD}	$I_S=300mA, V_{GS}=0V$			1.50	V
Input capacitance**	C_{iss}	$V_{DS}=10V, V_{GS}=0V, f=1MHz$			40	pF
Output capacitance**	C_{oss}				30	
Reverse Transfer capacitance**	C_{rss}				10	
SWITCHING TIME						
Turn-on Time**	td(on)	$V_{DD}=50V, R_L=250\Omega, V_{GS}=10V, R_{GS}=50\Omega, R_G=50\Omega$			10	ns
Turn-off Time**	td(off)				15	
Reverse recovery Time	trr	$V_{GS}=0V, I_S=300mA, V_R=25V, Dis/dt=-100a/uS$		30		ns
GATE-SOURCE ZENER DIODE						
Gate-Source Breakdown Voltage	BV_{GSO}	$I_{GS}=\pm 1mA$ (Open Drain)	± 21.5		± 30	V

* Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.

** These parameters have on way to verify.


2N7002KDW

SOT-363 PACKAGE OUTLINE Plastic surface mounted package



SYMBOL	MILLIMETER	
	MIN	MAX
A	0.900	1.100
A1	0.000	0.100
A2	0.900	1.000
b	0.150	0.350
c	0.080	0.150
D	2.000	2.200
E	1.150	1.350
E1	2.150	2.450
e	0.650 TYP.	
e1	1.200	1.400
L	0.525 REF.	
L1	0.260	0.460
theta	0°	8°

Precautions: PCB Design (Recommended land dimensions for SOT-363 diode. Electrode patterns for PCBs)



Note:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

Important Notice and Disclaimer

DOESHARE has used reasonable care in preparing the information included in this document, but DOESHARE does not warrant that such information is error free. DOESHARE assumes no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.

DOESHARE no warranty, representation or guarantee regarding the documents, circuits and products specification, DOESHARE reservation rights to make changes for any documents, products, circuits and specifications at any time without notice.

Purchasers are solely responsible for the choice, selection and use of the DOESHARE products and services described herein, and DOESHARE assumes no liability whatsoever relating to the choice, selection or use of the products and services described herein.

No license, express or implied, by implication or otherwise under any intellectual property rights of DOESHARE.

Resale of DOESHARE products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by DOESHARE for the DOESHARE product or service described herein and shall not create or extend in any manner whatsoever, any liability of DOESHARE.